

Sunsail 41.3

3 Cabins / 3 Heads

Specifications and Equipment List (Sunsail charter upgrades in bold)

Yacht Model:	Dufour 41
Length Overall:	41ft 9in 12.75m
Hull Length:	39ft 4in 11.99m
Beam:	14ft 1in 4.30m
Draft:	5ft 8in 1.75m
Fuel Capacity:	66 US Gal 250 L
Water Capacity:	66 US Gal 250 L
Engine:	Yanmar 45 HP



CONSTRUCTION

- Hull: Infused polyester/glassfibre
- Gelcoat: NPG Gelcoat with first layer impregnated with vinylester resin forming an optimum barrier against osmosis
- Structure: Inner moulded hull bottom, structural framing laminated to the hull
- Deck: Sandwich with injected core
- Ballast: Keel bolts reinforced by stainless steel backing plates
- Rudder: Semi-elliptical shape, filled with closed-cell epoxy foam
- Rudder stock: Solid stainless steel
- Non-slip deck surface: Diamond point non skid profile on deck
- Decoration: Sunsail graphics
- Shallow cast iron keel

DECK

- Stainless steel roof handrails
- Anchor locker: Self-draining with anchor chain eyebolt
- Bow pulpits: Stainless, opended for easy access
- Stern Pushpit: Lifebuoy bracket and opening life-lines with hook
- Stanchions: With 2 rows of life-lines
- Fixed bowsprit
- Stainless steel bow protection
- Lifeline gates and fender step

DECK FITTINGS

- Shroud chainplates: Outboard deck side shroud chainplates
- Stainless steel cleats
- Mooring line protection: 6 stainless steel plates, on hull sheer line
- Fuel deck fillers: 1
- Water deck fillers: 1

- Rigid boom vang
- Deck organisers: 4-sheave deck organiser for halyard, sheet, and reef line returns: 1 portside and 1 at starbord
- Cleats: 2 x 4 jam cleats port side and starboard side of the companionway
- Furler line jamcleats: 1 at aft end of sidedeck
- 1 electric halyard winch and 1 standard reefing line winch
- 2 electric sheet winches
- Reefing line system leads back to the roof
- Stainless steel anchor and galvanized chain
- Stainless steel exhaust
- GRP cover

COCKPIT

- Lockers: 2 large side lockers on starboard and portside
- Helm: Twin helm position with stainless steel wheels
- Helm console: Polyester POD and aluminium columns
- Engine control: Engine controls on side of cockpit and control panel on pod
- Compass: 1 compass on port helm position
- Instrumentation: On starboard and portside helm
- Gas locker: locker aft, to port
- Liferaft locker: Locker in transom
- Shore supply: Portside
- Bathing ladder: Foldaway stainless steel bathing ladder
- Cockpit floor: Non-slip polyester cockpit floor
- Emergency tiller: Head of rudder stock beneath helmsman's floor for fitting the emergency tiller
- Cockpit table
- Bimini and dodger
- Starboard and Portside helm console instrument support pods
- Cockpit shower (cold/hot)
- Aft bathing platform
- Transom protection
- 2 inflatable backrests for helmseat position
- Cockpit cushions (seat and backrest)
- Helmsman seat cushion
- Teak on seats
- Plancha and sink
- Cockpit portlight in aft starboard cabin
- Cockpit portlight in aft port side cabin
- Outboard crane and bracket

RIGGING & SAILS

- Sunsail enhanced mast: anodized aluminium with 2 levels of swept spreaders
- Mast stepping: On deck
- Lights: 3-colour masthead light + anchor light + steaming light
- Topping lift: Boom topping lift cleat
- Boom: Anodized aluminium fitted with 2 continuous reefers
- Standing rigging: Continuous in stainless single-strand cable, chrome-plated bronze rigging screws, comprising: forestay, i nter and lower shrouds
- Backstay
- Running rigging: Running rigging in pre-stretched textile including: main and genoa halyards, boom topping lift, main and genoa

INITIALS	INITIALS	REV: 10-02-2025
INITIALS	INITIALS	REV: 10-02-7075

sheets, 2 continuous reef lines, leech tensioner, furling line, downhaul tackle

- Custom heavy duty battened charter mainsail
- Charter upgrade, heavy duty furling genoa with UV protection strips
- Stackpack LazyJack system in Sunsail blue with logo
- Profurl genoa furler
- Mainsail bridle on coachroof

INTERIOR

- Woodwork: Real wood veneer
- Floors: Moabi laminated
- Doors: cabin doors can be secured in the open position
- Head-liner: Soft grey painted head-liner
- Signature ambiance
- Grey faux-leather upholstery

GLAZING & LIGHTING

- Hull: 10 hull windows
- Side Coachroof: 6 fixed ports and 2 openable
- Coachroof hatches: 1 size 44 and 4 size 10 Lewmar hatches with curtains
- 1 fixed porthole on the roof
- Lighting: Numerous downlights and reading lights
- Blinds with mosquito screens on deck hatches
- LED interior lights

COMPANIONWAY

- Steps: Wide steps
- Engine cover: Hinged wooden engine cover with 2 gas struts
- Hand rails: 2
- Wine cellar
- Custom companionway door

FORWARD CABIN

- 1 double bed
- Mattress: 14 cm thick foam mattress
- Stowage:
 - Below berth
 - 1 hanging locker with shelf
- Upholstery headboard
- Reading lights + indirect lighting
- Access: To sounding and speed transducers
- Access: To windlass

FORWARD HEAD

- Wash-basin: synthetic resin
- Water: Hot and cold water
- Large mirror
- Cupboards: Storage unit
- 1 Electric toilet
- Automatic shower pump

2 AFT HEADS

- Wash-basin: Basin unit with tap
- Water: Hot and cold water
- Large mirror
- 1 Electric toilet
- Automatic shower pump

SALOON

- Living room bench: Large seats
- Additional bench
- Saloon table convertible into berth
- Storage under seats and behind backrests
- Mast foot

GALLEY

- Worktop: synthetic resin
- Sink: Stainless twin-bowl sink with covers in synthetic resin
- Water: Hot and cold pumped water brass single-lever mixer tap
- Gas cooker: 2-burner gas cooker with oven on gimbals, with stainless rail
- Crockery storage: Dowels to retain crockery when heeling
- Cooler compressor 12V
- Refrigerator access: Via the worktop
- Stowage:
 - 2 closed cubby-holes
 - Below sink
 - Under floor
- Waste bin: Sort compartments
- Other: Light and ventilation ensured by opening port-lights and LED strips over galley
- Microwave
- Additional drawer fridge

AFT CABINS

- 1 double bed on port and starboard
- Mattress: 12 cm thick foam mattress with washable cover
- Fuel tank: Beneath starboard
- Water tank: Beneath port berth
- Stowage: Hanging locker
- Soundproofing: Double bulkhead provides acoustic and thermal insulation from adjoining engine compartment
- Technical area: Battery isolators on side of berth
- Mattress cover

ENGINE

- Engine: Yanmar 45 HP
- Transmission: Sail-drive
- Cooling system: Heat exchanger, anti-siphon valve
- Tank: Gauge on electrical distribution panel
- Fuel filter: Fuel filter with water separator
- Shut-off valve: Emergency fuel shut-off valve

- Control panel: Control panel close to helmsman, with hour meter and tachometer
- Alternator: Alternator with battery isolator
- Ventilation: Ventilation with 1 natural inlet and electric mechanical extract
- Bilge: Independent engine bilge
- Access: Access to the engine from front and both sides
- Propeller: 3-blade propeller, fixed
- Insulation: Carefully-designed foam acoustic and thermal insulation
- Rope cutter on Sail Drive

PLUMBING

- Water tanks: 1 polyethylene water tank with inspection holes and gauges
- Electric bilge pump: With strainer, controlled from electrical distribution panel
- Manual bilge pump: Operated from cockpit
- Hot water tank: Pressurized water pump unit and water-heater via heat-exchanger
- Other: Access to strainer via floor trap
- Water purifier
- Watermaker

ELECTRICITY

- Circuit: 12 V
- Distribution panel
- Isolator: 1 per battery set in aft port cabin
- 2000W inverter
- Shore power pack
- Increased battery capacity and AGM batteries in lieu of standard
- Battery charger
- USB outlets in the cabins
- LED navigation lights
- Electric windlass 2000W
- Full B&G electronic package
- Solar panels
- Stereo system with interior and exterior speakers
- Induction chargers in each cabin
- Generator
- Air conditioning
- AIS (transmitter/receiver)

GENERAL EQUIPMENT

- Mooring / dock lines / fenders
- Safety pack
- Charter pack
- Commissioning and delivery to charter base
- Custom antifouling

NOTE

The Builder reserves the right to change or amend the contents of this document at any time without prior notification to any third party, and no liability will be accepted for errors contained within the same.