


Sunsail 34.1

Specifications and Equipment List

Sunsail Charter Upgrades in BOLD

Length Overall: 35ft 4in 10.77m
Waterline Length: 31ft 2in 9.50m
Beam: 11ft 9in 3.57m
Draft: 4ft 11in 1.5m
Displacement: 12,046 lbs 5,470 kg
Fuel Capacity: 34 gal 130 L
Water Capacity: 95 gal 360 L
Sail Area: 531 sqft 49.3 sqm
Engine: 29hp



CONSTRUCTION

- Design in accordance with European Directive requirements and according to CE certification
- Monolithic hull design in polyester
- Monolithic structural inner moulding bonded to the hull
- Fibreglass and balsa wood sandwich contact deck, with diamond pattern non-slip coating
- Hull-deck join screwed, bonded and trimmed with 1 bulwark
- Cast iron keel fixed with bolts and stainless steel backing plates
- 2 Underhung rudders with stainless steel stock
- White coloured hull
- Cockpit table
- White oak Alpi version

DECK EQUIPMENT

- Standard mast 9/10 anodized aluminum deck stepped, 2 aft-swept spreaders Without backstay
- Anodised aluminum boom
- Discontinuous stainless steel standing rigging
- Rigid boom vang with tackle
- Self-tacking jib rigging with on-deck furler
- Mainsail stay rope on the roof (with 2 chainplates)
- 1 Self-tacking jib track with traveller
- Complete running rigging: Mainsail halyard, Genoa halyard with cleat on mast, Boom topping lift with cleat on mast, Mainsheet, 1 Self-tacking jib sheet
- 8 Clutches
- 2 Flag halyards
- 1 Self-tailing winch (H35.2 STA) to port, on the roof
- 1 winch handle
- 1 winch handle box
- Classic Dacron mainsail with Natural UV protection, cross cut, semi full batten
- Self-tacking jib Dacron with UV protection Natural, horizontal cut
- Lazy jacks
- Stainless steel pulpit 2 sections
- 2 Stainless steel pushpits
- 1 Lifebuoy support bracket

INITIALS_____

- Double guard lines and stainless steel stanchions
- Welded ring on pushpit for flag
- Emergency ladder on pushpit
- Self-draining cockpit
- 1 Cockpit locker under port side bench
- 2 Lockers in cockpit bottom
- Side helm's seats (aft helm seats in trim)
- 1 Liferaft locker to aft of cockpit
- Natural solid wood slatted cockpit benches
- "Luxe" polyester drop-leaf cockpit table
- Tilling positon: Stainless steel steering wheels Leather covered Steering gear at the helm station Steering line transmission system Stainless steel handrail 1 Cup holder
- 1 Steering compass to starboard of the companionway
- 2 Deck access points to tiller system
- 1 Emergency tiller
- Engine throttle and control panel on starboard
- 2 Hinged PMMA companionway doors Sliding hatch made of PMMA
- Fully opening transom, convertible to bathing platform
- Manual opening using hoist, assisted by 2 pull cylinders
- Teak decking on swim deck
- 1 Fixed, telescopic stainless steel swimming ladder
- Teak slatted aft platform
- Teak slatted helm seats
- 1 Halyard bag (to port)
- Hot/cold water cockpit shower
- Aft transom protection
- Bow stainless steel protection
- Outboard engine bracket
- Aft fairleads
- Access opening to port and startboard

SALOON

- GRP saloon companionway coated with non-slip surface on the steps
- 2 Stainless steel handrails covered with anthracite leather
- 2 Lengthways saloon bench sets, can be used as a single berth
- Saloon table with 2 drop-leaves and 2 central top-access storage spaces
- Storage under bench seats
- 2 LED ceiling lights
- 1 USB socket on the 12V electrical panel
- 2 Panoramic roof windows
- 2 Hull portholes with curtain
- 1 Flush deck hatch with fan, T44, blind and mosquito net
- LED indirect lighting
- Macadamia padding upholstery (saloon & cabins)

GALLEY

- L-shaped galley To starboard
- Worktop in compact Clay with painted wooden fiddles
- 1 rectangular stainless steel sink (320mm x 300mm / 1'1" x 1')
- 1 Mixer tap with hot/cold water under pressure
- Stainless steel 2 burner oven/grill cooker on gimbal
- Cool box 100 L / 26 gal top opening (Positive cold)
- Storage and lockers
- 1 Dual compartment slide-out bin (2 x 15L / 2 x 4 gal)
- 1 230 V socket

- 1 Opening porthole on coaming in the side window with mosquito net
- Compact sink cover with cutting board
- Sea water foot pump with cool box draining function

CHART TABLE

- Chart table with folding tray against the starboard bulkhead with shelves fitted with fiddles in the upper part
- 12 V electrical panel nearby
- 1 Adjustable LED spotlight
- 1 230 V socket
- Single USB socket
- Fixed coaming window with pleated blind

OWNER'S CABIN

- 1 Central double bed (2,02m x 1,60m 0,55m / 6'8" x 5'3" 1'10")
- 2 Hanging closets with 1 open shelf on top, open lockers along the hull
- 2 Adjustable LED spotlights in the headboard
- 1 dual USB port outlet on each side of the bed
- 1 230 V socket to port
- 1 Flush deck hatch with fan, T44, blind and mosquito net
- 2 Hull portholes with curtain
- Double door

STARBOARD AFT CABIN

- 1 Double bed (2,00m x 1,60m x 1,30m / 6'7" x 5'3" x 4'3")
- 1 Hanging closet with 1 open shelf on the top
- 1 Bed access sideboard
- 2 Adjustable LED spotlights in the headboard
- 1 dual USB port
- 1 230 V socket
- 1 Opening porthole on the cockpit coaming + Mosquito screens
- 1 Opening porthole below cockpit seat with curtain
- Mosquito nets for opening portholes

AFT PORT SIDE HEAD

- Shower with plexiglass door Self-draining storage bin 1 Mixer tap White polyester shower base
- 1 Manual toilet
- 1 80 L / 21 gal rigid holding tank
- 1 Polyester basin 1 Hot/cold water mixer tap
- 1 Cabinet
- 1 Mirror
- Toilet accessories
- 1 Opening porthole in coaming
- 2 LED ceiling lights
- 1 230 V socket

ENGINE

- 29 HP Engine Yanmar Diesel (Propeller shaft)
- Engine control Control panel in cockpit (To starboard)
- Engine compartment: Soundproofing foam Ventilation: 2 Air intakes and 1 powered air expulsion
- 1 Alternator (12V / 125Ah)
- 1 Rotomoulded diesel tank 130 L / 34 gal (below aft starboard cabin berth) Gauge on electrical panel 1 Deck filler
- Filters: Seawater Diesel Water separator
- Stainless steel shaft line
- Fixed three blades propeller
- 1 Engine access through companionway (opening with 2 gas struts)

INITIALS_____

- 2 Access to side engine: Head & Aft cabin

ELECTRICAL INSTALLATION

- 12V circuit
- 1 AGM service battery (75Ah) 1 AGM engine battery (50Ah)
- 1 Power distributor
- 12 V electrical panel (Fuses Voltmeter 1 Fuel gauge)
- 1 Single USB socket at chart table
- LED lighting: Overhead lights, Adjustable spotlight in cabins & at chart table
- LED navigation lights: 1 Masthead light 1 Engine navigation light 1 Anchor light on masthead
- Shore power air conditioning
- Electric toilet
- Hifi + Interior loudspeakers & Waterproof exterior speakers
- Dual USB socket: 1 in the saloon, 2 in the forward cabin, 1 in the aft cabins
- 40 Amperes battery charger
- 2 AGM service batteries 100 Ah (in lieu of standard 75 Ah)
- 1 000 W Electric windlass + Remote control
- Fans in saloon & cabins
- Raymarine Instrument Package
- Solar panel

PLUMBING

- 1 Rotomoulded freshwater tank 206 L / 54 gal, under berth in forward cabin
- Electrical gauge on 12 V panel
- 1 Deck filler
- Pressurised electric water pump Expansion tank Inline filter
- 25 L / 7 gal Electric water heater (engine use) below saloon starboard bench
- 1 80 L / 21 gal rigid holding tank
- 1 Electric bilge pump 1 Manual bilge pump
- 1 Electric shower drain pump
- Additional fresh water tank (130L / 53 gal)

GAS

- Gas cylinder locker starboard aft cockpit
- Regulator and safety tap
- Gas leak detector

GENERAL EQUIPMENT

- Mooring / dock lines / fenders
- Safety pack
- Charter pack
- Commissioning and delivery to charter base

NOTE

The Builder reserves the right to change or amend the contents of this document at any time without prior notification to any third party, and no liability will be accepted for errors contained within the same.